

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
14 October 2004 (14.10.2004)

PCT

(10) International Publication Number
WO 2004/087384 A1

(51) International Patent Classification⁷: **B26F 1/20**,
D04H 13/00, D06C 15/02

(21) International Application Number:
PCT/IT2003/000198

(22) International Filing Date: 2 April 2003 (02.04.2003)

(25) Filing Language: Italian

(26) Publication Language: English

(71) Applicant and

(72) Inventor: **GIACOMETTI, Claudio** [IT/IT]; Via
Falserone, 13, I-51100 Pistoia (IT).

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:


— with international search report

(74) Agents: **MANNUCCI, Michele** et al.; Ufficio tecn. Ing
A. Manucci S.r.l., Via della Scala, 4, I-50123 Firenze (IT).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: METHOD AND DEVICE TO PRODUCE A PERFORATED WEB MATERIAL



(57) Abstract: A method to produce a perforated web material, wherein the web material (N) is fed through a nip (11) between a first roller (7) and a second roller (9) rotating in opposite directions and pressed against each other, the first roller (7) being provided with protuberances (7P) for perforation. Characteristically, the web material is heated before being fed into said nip.